Bush Hog® TOUGH 2426QT Quick Attach Front-Push Loaders Bush Hog Quick Attach System

**BUSH HOG® TOUGH FEATURES TOUGH Boxed Boom Design TOUGH Large Diameter Cross Tubes TOUGH Robotic Welds TOUGH High Strength Chrome Plated Cylinder Rods TOUGH Powder Coat Paint** 



MODEL Specifications Based on 1997 ASAE STANDARD	os <b>2426QT</b>
Tractor PTO HP Range	35 - 75
2WD/FWA	2WD only
Maximum Lift Height - Measured at Pivot Pin	117 inches
Maximum Lift Height - Under Level Bucket	108 inches
Maximum Dump Angle	50°
Digging Depth	4.5 inches
Lift Capacity to Maximum Height - At Pivot Pin	2990 lbs
Lift Capacity to Maximum Height - 31.5 inches Forward of Pivot Pin	1920 lbs
Lift Capacity to 59 inch Height - At Pivot Pin	4130 lbs
Lift Capacity to 59 inch Height - 31.5 inches Forward of Pivot Pin	3020 lbs
Breakout Force - At Pivot Pin	4985 lbs
Breakout Force - 31.5 inches - Forward of Pivot Pin	3500 lbs
Rollback Force at Maximum Height - 31.5 inches Forward of Pivot Pin	2400 lbs
Rollback Force at 59 inch Height - 31.5 inches Forward of Pivot Pin	3340 lbs
Rollback Force at Ground Level - 31.5 inches Forward of Pivot Pin	2710 lbs
Raising Time (Ground Level to Full Height)	6 seconds
Lowering Time (Full Height to Ground Level)	3 seconds
Bucket Dumping Time (Full Rollback to Full Dump)	3.5 seconds
Bucket Rollback Time (Full Dump to Full Rollback)	2 seconds
Hydraulics Two 2.0 inch Bore, 23.19 inch Stroke Double Acting	g Bucket Cylinders and Two 2.25 inch Bore, 29.62 inch Stroke Double Acting Lift Cylinders
Specifications Based on Tractor System of	2450 PSI hyd. Pressure & 11 GPM pump capacity
Bush Hog Quick Attach Buckets	Available in 60, 72 and 80 inch widths
Bush Hog Quick Attach Heavy Duty Buckets	Available in 60, 72 and 84 inch widths
	hment (42 inch tines), Round Bale Spear, Grapple Fork, Bucket Tine Teeth, Side Cutting Edges, Spill Guard Attachment, Hydraulic Self-Leveling, and Grill Guards

Warranty 1 year limited warranty

FEATURES Available in major tractor colors